



SAFETY DATA SHEET

1. Identification

| | |
|---|---|
| Product identifier | Sani Luxe Hand Sanitizer Gel |
| Other means of identification | |
| Part Number | LB-4000 |
| Recommended use | Not available. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Supplier | |
| Company Name | Celeste Industries Corporation |
| Address | 8221 Teal Drive, suite 405 Easton, Maryland 21601 (USA) 410-822-5775 (inside U.S.A) 1-410-822-5775 (outside U.S.A.) |
| Email | info@celestecorp.com |
| In Case of Emergency | CHEMTREC (24 hours) within USA and CANADA: 1-800-424-9300 Outside USA and Canada (collect call accepted): 1-703-527-3883 |

2. Hazard(s) identification

| | | |
|------------------------------|-------------------|------------|
| Physical hazards | Flammable liquids | Category 3 |
| Health hazards | Not classified. | |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|--|---|
| Signal word | Warning |
| Hazard statement | Flammable liquid and vapor. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. |
| Response | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use appropriate media to extinguish. |
| Storage | Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|----------------------|---------------------------------|-------------------|----------|
| Ethyl Alcohol | | 64-17-5 | 60 - 65 |

4. First-aid measures

| | |
|-------------------|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
|-------------------|---|

| | |
|---|---|
| Skin contact | Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Headache. Direct contact with eyes may cause temporary irritation. Coughing. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. |
| General information | Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Flammable liquid and vapor. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|------------------------------|------|------------------------|
| CYCLOHEXANE (CAS 110-82-7) | PEL | 1050 mg/m3 300 ppm |
| Ethyl Acetate (CAS 141-78-6) | PEL | 1400 mg/m3 400 ppm |
| Ethyl Alcohol (CAS 64-17-5) | PEL | 1900 mg/m3 1000 ppm |
| t-Butanol (CAS 75-65-0) | PEL | 300 mg/m3 100 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|------------------------------|------|----------|
| ACRYLIC ACID (CAS 79-10-7) | TWA | 2 ppm |
| CYCLOHEXANE (CAS 110-82-7) | TWA | 100 ppm |
| Ethyl Acetate (CAS 141-78-6) | TWA | 400 ppm |
| Ethyl Alcohol (CAS 64-17-5) | STEL | 1000 ppm |
| t-Butanol (CAS 75-65-0) | TWA | 100 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|------------------------------|------|------------------------|
| ACRYLIC ACID (CAS 79-10-7) | TWA | 6 mg/m3 2 ppm |
| CYCLOHEXANE (CAS 110-82-7) | TWA | 1050 mg/m3 300 ppm |
| Ethyl Acetate (CAS 141-78-6) | TWA | 1400 mg/m3 400 ppm |
| Ethyl Alcohol (CAS 64-17-5) | TWA | 1900 mg/m3 1000 ppm |
| t-Butanol (CAS 75-65-0) | STEL | 450 mg/m3 150 ppm |
| | TWA | 300 mg/m3 100 ppm |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Acrylic Acid (CAS 79-10-7)

Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

Acrylic Acid (CAS 79-10-7)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Acrylic Acid (CAS 79-10-7)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Acrylic Acid (CAS 79-10-7)

Can be absorbed through the skin.

| | |
|--|--|
| Appropriate engineering controls | Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. |
| Other | Wear appropriate chemical resistant clothing. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

Appearance

| | |
|---|------------------------|
| Physical state | Not available. |
| Form | Liquid. Gel. |
| Color | Colorless |
| Odor | Citrus |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Flash point | 97.0 °F (36.1 °C) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | 0.89 g/cm ³ |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | Carbon oxides. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Not available. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Expected to be a low ingestion hazard. |

Symptoms related to the physical, chemical and toxicological characteristics
Headache. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

| Components | Species | Test Results |
|------------------------------|----------------|-------------------------------------|
| Acrylic Acid (CAS 79-10-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 1000 mg/kg, 24 Hours |
| Inhalation | | |
| <i>Vapor</i> | | |
| LC50 | Rat | > 4.3 mg/l, 1 Hours |
| Oral | | |
| LD50 | Rat | 150 - 470 mg/kg |
| Cyclohexane (CAS 110-82-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| <i>Vapor</i> | | |
| LC50 | Rat | > 33000 mg/m ³ , 4 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Ethyl Acetate (CAS 141-78-6) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 20000 mg/kg, 24 Hours |
| Oral | | |
| LD50 | Rat | 5.6 g/kg |

| Components | Species | Test Results |
|---|--|---|
| Ethyl Alcohol (CAS 64-17-5) | | |
| Acute | | |
| Inhalation | | |
| Vapor | | |
| LC50 | Rat | 51 mg/l, 6 Hours |
| t-Butanol (CAS 75-65-0) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 3.5 g/kg |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Not classifiable as to carcinogenicity to humans. | |
| ACGIH Carcinogens | | |
| Acrylic Acid (CAS 79-10-7) | | A4 Not classifiable as a human carcinogen. |
| t-Butanol (CAS 75-65-0) | | A4 Not classifiable as a human carcinogen. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Acrylic Acid (CAS 79-10-7) | | 3 Not classifiable as to carcinogenicity to humans. |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) | | |
| | Not listed. | |
| US. National Toxicology Program (NTP) Report on Carcinogens | | |
| | Not listed. | |
| Reproductive toxicity | Possible reproductive hazard. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not available. | |
| Chronic effects | Prolonged inhalation may be harmful. | |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|------------------------------|---------|---|
| Cyclohexane (CAS 110-82-7) | | |
| Aquatic | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours |
| Ethyl Acetate (CAS 141-78-6) | | |
| Aquatic | | |
| Fish | LC50 | Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours |
| Ethyl Alcohol (CAS 64-17-5) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 7.7 - 11.2 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours |
| t-Butanol (CAS 75-65-0) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 4607 - 6577 mg/l, 48 hours |

| Components | Species | Test Results |
|--|--|--|
| Fish | LC50 | Fathead minnow (<i>Pimephales promelas</i>) 6130 - 6700 mg/l, 96 hours |
| Persistence and degradability | No data is available on the degradability of any ingredients in the mixture. | |
| Bioaccumulative potential | | |
| Partition coefficient n-octanol / water (log Kow) | | |
| Acrylic Acid | | 0.35 |
| Cyclohexane | | 3.44 |
| Ethyl Acetate | | 0.73 |
| Ethyl Alcohol | | -0.31 |
| t-Butanol | | 0.35 |
| Mobility in soil | Not established. | |
| Other adverse effects | None known. | |
| 13. Disposal considerations | | |
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| Local disposal regulations | Dispose in accordance with all applicable regulations. | |
| Hazardous waste code | D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company. | |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). | |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. | |

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | Flammable liquids, n.o.s. (Ethyl Alcohol) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | III |
| Environmental hazards | |
| Marine pollutant | No |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | B1, B52, IB3, T4, TP1, TP29 |
| Packaging exceptions | 150 |
| Packaging non bulk | 203 |
| Packaging bulk | 242 |

IATA

| | |
|-------------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | Flammable liquid, n.o.s. (Ethyl Alcohol) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | No |
| ERG Code | 3L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed with restrictions. |
| Cargo aircraft only | Allowed with restrictions. |

IMDG

| | |
|--|---|
| UN number | UN1993 |
| UN proper shipping name | FLAMMABLE LIQUID, N.O.S. (Ethyl Alcohol) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | |
| Marine pollutant | no |
| EmS | F-E, S-E |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. Not applicable. |

DOT



IATA; IMDG



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|------------------------------|---------|
| Acrylic Acid (CAS 79-10-7) | Listed. |
| Cyclohexane (CAS 110-82-7) | Listed. |
| Ethyl Acetate (CAS 141-78-6) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Acrylic Acid (CAS 79-10-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethyl Acetate (CAS 141-78-6) Low priority

Ethyl Alcohol (CAS 64-17-5) Low priority

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Acrylic Acid (CAS 79-10-7)

Cyclohexane (CAS 110-82-7)

Ethyl Acetate (CAS 141-78-6)

Ethyl Alcohol (CAS 64-17-5)

t-Butanol (CAS 75-65-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acrylic Acid (CAS 79-10-7)

Cyclohexane (CAS 110-82-7)

Ethyl Acetate (CAS 141-78-6)

t-Butanol (CAS 75-65-0)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 09-10-2020

Version # 01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Celeste Industries cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.