

Case Study

BEFORE AND AFTER

Successful sealant removal with EcoClean



HOW TO ORDER ECO-CLEAN

Contact your Celeste Account Representative or contact us at:

1-800-447-5775
www.celestecorp.com

USAGE

Sealant Remover

APPLICATION

EcoClean works by using a proprietary blend of aprotic solvents to gently soften and loosen polysulfide sealants making them easy to remove with a traditional scraper. Simply apply, let it dwell, and remove! Available in liquid or gel.



ISSUE

Traditional methods of sealant removal are time consuming, and waste precious man hours. Customer struggled with sealant removal on several aircraft components.



RESOLUTION

After a short 20 minute dwell, EcoClean softened sealants to allow quicker removal with a scraper.



Celeste Part #	Description	Case Specification	Pallet Specification
SP-ECLN/QT	EcoClean Liquid 12 x quart bottles per case	14 x 11 x 11 in, x 26 lbs (36 x 28 x 28 cm, x 12 kg)	11 cases x 4 layers, 53 in (153 cm) height
SP-ECLNGL/QT	EcoClean Gel 12x quart bottles per case	14 x 11 x 11 in, x 26 lbs (36 x 28 x 28 cm, x 12 kg)	11 cases x 4 layers, 53 in (153 cm) height