# **SAFETY DATA SHEET**



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Sani Luxe Hand Sanitizer Gel

Registration number

Synonyms None.

Oynonymo mono.

Part Number TR-BR06, TR-BR08, TR-BR12, TR-BR40, TR-BR40/CA, TR-BR40/GAL, (Formula: LB-4000)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesHand sanitizer.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Wynn's Belgium BV
Address Industriepark-West 46

B-9100 Sint-Niklaas, Belgium

**Telephone** +1-410-822-5775

Manufacturer

Company name Celeste Industries Corporation

Address 8007 Industrial Park Rd

Easton, Maryland 21601 (USA)

Telephone +1-410-822-5775
Email info@celestecorp.com

1.4. Emergency telephone

number

CHEMTREC (24 hours) within USA and CANADA 1-800-424-9300

Outside USA and Canada (collect call accepted): 1-703-527-3883

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 3 H226 - Flammable liquid and

vapour.

**Health hazards** 

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

#### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Ethyl alcohol

**Hazard pictograms** 



Signal word Warning

**Hazard statements** 

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

#### **Precautionary statements**

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

Material name: Sani Luxe Hand Sanitizer Gel

P243 Take action to prevent static discharges.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use appropriate media to extinguish.

**Storage** 

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal** Not assigned.

Supplemental label information EUH208 - Contains (R)-p-Mentha-1,8-diene. May produce an allergic reaction.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethyl alcohol	45 - 70	64-17-5 200-578-6	01-2119457610-43-0569	603-002-00-5	
Classif	cation: Flam. Liq.	2;H225, Eye Irrit. 2;⊢	1319		
(R)-p-Mentha-1,8-diene	0,2	5989-27-5 227-813-5	-	601-029-00-7	
Classif			H315, Skin Sens. 1;H317, A Aquatic Chronic 1;H410	sp. Tox.	С
Other components below repolevels	rtable 42.11				

# List of abbreviations and symbols that may be used above

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

#### **SECTION 4: First aid measures**

**General information**Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

## 4.1. Description of first aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

Symptoms may be delayed.

#### **SECTION 5: Firefighting measures**

General fire hazards Flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

media

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Unsuitable extinguishing

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

#### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

# 6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

# 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13.

# **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

1000 ppm

Storage class (TRGS 510): 3 (Flammable liquids)

7.3. Specific end use(s)

Hand sanitizer.

#### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	Ceiling	3800 mg/m3
		2000 ppm
	MAK	1900 mg/m3
		1000 ppm
Belgium. Exposure Limit Values		
Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm
Bulgaria. OELs. Regulation No 13 on	protection of workers aga	inst risks of exposure to chemical agents at work
Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1000 mg/m3
Croatia. Dangerous Substance Expo	sure Limit Values in the Wo	orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09
Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	MAC	1900 mg/m3

Components	nt Decree 361 Type	Value
Ethyl alcohol (CAS 64-17-5)	Ceiling	3000 mg/m3
	TWA	1000 mg/m3
Denmark. Exposure Limit Values Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	TLV	1900 mg/m3
Litty alcohol (CAS 04-17-5)	ILV	1000 ppm
Estonia. OELs. Occupational Expo Components	osure Limits of Hazardous Sub Type	ostances (Regulation No. 105/2001, Annex), as amende Value
Ethyl alcohol (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3
		500 ppm
Finland. Workplace Exposure Lim	its	
Components	Туре	Value
R)-p-Mentha-1,8-diene CAS 5989-27-5)	STEL	280 mg/m3
,		50 ppm
	TWA	140 mg/m3
		25 ppm
Ethyl alcohol (CAS 64-17-5)	STEL	2500 mg/m3
		1300 ppm
	TWA	1900 mg/m3
		1000 ppm
	(I ED) ( O ( I E	• •
Components	Туре	ure to Chemicals in France, INRS ED 984 Value
Components Ethyl alcohol (CAS 64-17-5)	<b>Type</b> VLE	ure to Chemicals in France, INRS ED 984
Components Ethyl alcohol (CAS 64-17-5)	Туре	value 9500 mg/m3
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative	<b>Type</b> VLE	ure to Chemicals in France, INRS ED 984 Value
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative	Type  VLE e limit (VL)	value 9500 mg/m3
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Regulatory status: Indicative	Type  VLE e limit (VL) e limit (VL)	9500 mg/m3 5000 ppm
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Regulatory status: Indicative	Type  VLE e limit (VL) e limit (VL)  VME	9500 mg/m3 5000 ppm
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Regulatory status: Indicative  Regulatory status: Indicative  Regulatory status: Indicative	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative	Type  VLE e limit (VL)  vME e limit (VL)  vinit (VL)  e limit (VL) e limit (VL)  v OELs). Commission for the Ir	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Germany. DFG MAK List (advisory in the Work Area (DFG)  Components	Type  VLE e limit (VL)  VME e limit (VL)  vME e limit (VL) e limit (VL)  v OELs). Commission for the In	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Components (DFG)  Components  R)-p-Mentha-1,8-diene	Type  VLE e limit (VL)  vME e limit (VL)  vinit (VL)  e limit (VL) e limit (VL)  v OELs). Commission for the Ir	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Components Indicative  Components  R)-p-Mentha-1,8-diene	Type  VLE e limit (VL)  VME e limit (VL)  vME e limit (VL) e limit (VL)  v OELs). Commission for the In	ure to Chemicals in France, INRS ED 984 Value  9500 mg/m3  5000 ppm  1900 mg/m3  1000 ppm  nvestigation of Health Hazards of Chemical Compound  Value
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Germany. DFG MAK List (advisory on the Work Area (DFG)  Components  (R)-p-Mentha-1,8-diene  CAS 5989-27-5)	Type  VLE e limit (VL)  VME e limit (VL)  vME e limit (VL) e limit (VL)  v OELs). Commission for the In	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1vestigation of Health Hazards of Chemical Compound Value 28 mg/m3
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Germany. DFG MAK List (advisory on the Work Area (DFG)  Components  (R)-p-Mentha-1,8-diene  CAS 5989-27-5)	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL) e limit (VL)  VOELs). Commission for the Interpretation  Type  TWA	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1000 ppm  value  Value  28 mg/m3 5 ppm
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Company. DFG MAK List (advisory  In the Work Area (DFG)  Components  R)-p-Mentha-1,8-diene  (CAS 5989-27-5)  Ethyl alcohol (CAS 64-17-5)  Germany. TRGS 900, Limit Values	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1000 ppm  value 28 mg/m3 5 ppm 380 mg/m3 200 ppm
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Germany. DFG MAK List (advisory n the Work Area (DFG)  Components  R)-p-Mentha-1,8-diene  CAS 5989-27-5)  Ethyl alcohol (CAS 64-17-5)  Germany. TRGS 900, Limit Values  Components	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA  TWA	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1vestigation of Health Hazards of Chemical Compound Value 28 mg/m3 5 ppm 380 mg/m3 200 ppm
Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Company. DFG MAK List (advisory  In the Work Area (DFG)  Components  (R)-p-Mentha-1,8-diene  CAS 5989-27-5)  Ethyl alcohol (CAS 64-17-5)  Germany. TRGS 900, Limit Values  Components  (R)-p-Mentha-1,8-diene	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA  TWA  in the Ambient Air at the Worl  Type	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1vestigation of Health Hazards of Chemical Compound Value 28 mg/m3 5 ppm 380 mg/m3 200 ppm  kplace Value 28 mg/m3
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Germany. DFG MAK List (advisory  n the Work Area (DFG)  Components  (R)-p-Mentha-1,8-diene (CAS 5989-27-5)  Germany. TRGS 900, Limit Values  Components  (R)-p-Mentha-1,8-diene (CAS 5989-27-5)	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA  TWA  in the Ambient Air at the Worl  Type  AGW	pre to Chemicals in France, INRS ED 984 Value  9500 mg/m3  5000 ppm  1900 mg/m3  1000 ppm  nvestigation of Health Hazards of Chemical Compound Value  28 mg/m3  5 ppm  380 mg/m3  200 ppm  kplace  Value  28 mg/m3  5 ppm  5 ppm
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Indicati	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA  TWA  in the Ambient Air at the Worl  Type	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1vestigation of Health Hazards of Chemical Compound Value 28 mg/m3 5 ppm 380 mg/m3 200 ppm  kplace Value 28 mg/m3
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Germany. DFG MAK List (advisory  n the Work Area (DFG)  Components  (R)-p-Mentha-1,8-diene (CAS 5989-27-5)  Germany. TRGS 900, Limit Values  Components  (R)-p-Mentha-1,8-diene (CAS 5989-27-5)	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA  TWA  in the Ambient Air at the Worl  Type  AGW	pre to Chemicals in France, INRS ED 984 Value  9500 mg/m3  5000 ppm  1900 mg/m3  1000 ppm  nvestigation of Health Hazards of Chemical Compound Value  28 mg/m3  5 ppm  380 mg/m3  200 ppm  kplace  Value  28 mg/m3  5 ppm  5 ppm
Ethyl alcohol (CAS 64-17-5) Regulatory status: Indicative Regulato	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the Ir  Type  TWA  TWA  TWA  TWA  in the Ambient Air at the Worl  Type  AGW  AGW	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1000 ppm  value  28 mg/m3 5 ppm 380 mg/m3 200 ppm  kplace  Value  28 mg/m3 5 ppm 380 mg/m3 200 ppm
Components  Ethyl alcohol (CAS 64-17-5)  Regulatory status: Indicative  Regulatory status: Indicative  Regulatory status: Indicative  Regulatory status: Indicative	Type  VLE e limit (VL)  VME e limit (VL)  VME e limit (VL)  OELs). Commission for the Ir  Type  TWA  TWA  TWA  TWA  in the Ambient Air at the Worl  Type  AGW  AGW	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 1000 ppm  value  28 mg/m3 5 ppm 380 mg/m3 200 ppm  kplace  Value  28 mg/m3 5 ppm 380 mg/m3 200 ppm
Ethyl alcohol (CAS 64-17-5) Regulatory status: Indicative Germany. DFG MAK List (advisory in the Work Area (DFG) Components (R)-p-Mentha-1,8-diene (CAS 5989-27-5) Ethyl alcohol (CAS 64-17-5)  Germany. TRGS 900, Limit Values Components (R)-p-Mentha-1,8-diene (CAS 5989-27-5) Ethyl alcohol (CAS 64-17-5)	Type  VLE e limit (VL)  WME e limit (VL)  VME e limit (VL)  OELs). Commission for the In  Type  TWA  TWA  TWA  TWA  in the Ambient Air at the Worl Type  AGW  AGW  AGW  AGW	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm  Neestigation of Health Hazards of Chemical Compound Value 28 mg/m3 5 ppm 380 mg/m3 200 ppm  kplace Value 28 mg/m3 5 ppm 380 mg/m3 200 ppm

Hungary. OELs. Joint Decree on Chemical Components	Safety of Workplaces Type	Value
Ethyl alcohol (CAS 64-17-5)	STEL	3800 mg/m3
	TWA	1900 mg/m3
celand. OELs. Regulation 154/1999 on occomponents	cupational exposure limits Type	Value
thyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
eland. Occupational Exposure Limits omponents	Туре	Value
thyl alcohol (CAS 64-17-5)	STEL	1000 ppm
taly. Occupational Exposure Limits Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm
atvia. OELs. Occupational exposure limit	values of chemical substances in Type	work environment Value
Ethyl alcohol (CAS 64-17-5)	TWA	1000 mg/m3
Lithuania. OELs. Limit Values for Chemica Components	al Substances, General Requireme Type	ents Value
Ethyl alcohol (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3
		500 ppm
letherlands. OELs (binding) Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	STEL	1900 mg/m3
	TWA	260 mg/m3
Iorway. Administrative Norms for Contam Components	inants in the Workplace Type	Value
R)-p-Mentha-1,8-diene	TLV	140 mg/m3
CAS 5989-27-5)		25
Tabul alaabal (CAS CA 47 F)	TIN	25 ppm
Ethyl alcohol (CAS 64-17-5)	TLV	950 mg/m3
Poland. Ordinance of the Minister of Labor concentrations and intensities of harmful	health factors in the work environi	ment, Journal of Laws 2014, item 817
Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		0 ppm
Portugal. VLEs. Norm on occupational exp Components	Туре	6) Value
Ethyl alcohol (CAS 64-17-5)	TWA	1000 ppm
Romania. OELs. Protection of workers from Components	m exposure to chemical agents at Type	the workplace Value
Ethyl alcohol (CAS 64-17-5)	STEL	9500 mg/m3
		5000 ppm
	TWA	1900 mg/m3
		1000 ppm
Slovakia. OELs. Regulation No. 300/2007 o Components	concerning protection of health in Type	work with chemical agents Value
Ethyl alcohol (CAS 64-17-5)	STEL	1920 mg/m3
	- ·	. 5 = 6 1119/1110

Components	Туре	Value
		1000 ppm
	TWA	960 mg/m3
		500 ppm
Slovenia. OELs. Regulation (Official Gazette of the Repu		against risks due to exposure to chemicals while work
Components	Туре	Value
(R)-p-Mentha-1,8-diene (CAS 5989-27-5)	TWA	28 mg/m3
		5 ppm
Ethyl alcohol (CAS 64-17-5)	TWA	960 mg/m3
		500 ppm
Spain. Occupational Exposi	ure Limits	
Components	Туре	Value
(R)-p-Mentha-1,8-diene (CAS 5989-27-5)	TWA	168 mg/m3
		30 ppm
Ethyl alcohol (CAS 64-17-5)	STEL	1910 mg/m3
		1000 ppm
Sweden. OELs. Work Enviro Components	onment Authority (AV), Occupationa Type	al Exposure Limit Values (AFS 2015:7) Value
Ethyl alcohol (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3
		500 ppm
Switzerland. SUVA Grenzwe	erte am Arbeitsplatz	
Components	Туре	Value
(R)-p-Mentha-1,8-diene (CAS 5989-27-5)	STEL	80 mg/m3
		14 ppm
	TWA	40 mg/m3
		7 ppm
Ethyl alcohol (CAS 64-17-5)	STEL	1920 mg/m3
,		1000 ppm
	TWA	960 mg/m3
		500 ppm
UK. EH40 Workplace Expos	ure Limits (WELs)	
Components	Туре	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1920 mg/m3
,		1000 ppm
ogical limit values	No biological exposure limits noted	• •
ommended monitoring cedures	Follow standard monitoring procedu	
ved no effect levels (DNELs	)	
General Population		

Components	Value	Assessment factor	Notes
Ethyl alcohol (CAS 64-17-5)			
Long-term, Systemic, Inhalation	114 mg/m3		Carcinogenicity
Workers			
Components	Value	Assessment factor	Notes
Components Ethyl alcohol (CAS 64-17-5)	Value	Assessment factor	Notes

Predicted no effect concentrations (PNECs) Not available.

**Exposure guidelines** 

Germany DFG MAK (advisory): Skin designation

(R)-p-Mentha-1,8-diene (CAS 5989-27-5) Can be absorbed through the skin.

Germany TRGS 900 Limit Values: Skin designation

(R)-p-Mentha-1.8-diene (CAS 5989-27-5) Can be absorbed through the skin.

Netherlands OELs (binding): Skin designation

Ethyl alcohol (CAS 64-17-5) Can be absorbed through the skin.

Slovenia, OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

(R)-p-Mentha-1,8-diene (CAS 5989-27-5) Can be absorbed through the skin.

Spain OELs: Skin designation

(R)-p-Mentha-1,8-diene (CAS 5989-27-5) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection should meet standard EN 166.

Skin protection

Wear appropriate chemical resistant gloves. Wear suitable gloves tested to EN374. - Hand protection

- Other Wear suitable protective clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Follow guidance on selection, use, care

and maintenance in accordance with EN 529.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Hygiene measures When using do not smoke.

**Environmental exposure** 

controls

Odour

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state Liquid. Gel. **Form** Colourless. Colour Citrus

Melting point/freezing point Property has not been measured. > 78 °C (> 172.4 °F) estimated Boiling point or initial boiling

point and boiling range

Flammability (solid, gas) Flammable liquid and vapour.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Property has not been measured. Explosive limit - upper Property has not been measured.

(%)

Flash point

36,1 °C (97,0 °F) Closed cup

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable.

Property has not been measured. Kinematic viscosity Property has not been measured.

Solubility(ies)

Solubility (water) Soluble in water. Partition coefficient

(n-octanol/water)

Not applicable.

Vapour pressure Property has not been measured. Property has not been measured. Vapour density

0,89 g/m<sup>3</sup> Relative density Not available. Particle characteristics

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

2.7 **Evaporation rate** 

Not explosive. **Explosive properties** Not oxidising. Oxidising properties

### **SECTION 10: Stability and reactivity**

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the 10.4. Conditions to avoid

decomposition temperature. Avoid temperatures exceeding the flash point. Contact with

incompatible materials.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous

decomposition products

Carbon oxides.

# **SECTION 11: Toxicological information**

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact The product contains a small amount of sensitizing substance which may provoke an allergic

reaction among sensitive individuals in contact with skin.

Eye contact Causes serious eye irritation.

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

**Symptoms** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

#### 11.1. Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species **Test Results** 

(R)-p-Mentha-1,8-diene (CAS 5989-27-5)

**Acute** Oral

Rat > 2000 ma/ka LD50

Ethyl alcohol (CAS 64-17-5)

**Acute** Inhalation

Vapour

LC50 Rat 53 mg/l, 6 Hours

Oral

LD50 Rat > 7700 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation

Not a respiratory sensitiser.

Skin sensitisation

This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

#### Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

(R)-p-Mentha-1,8-diene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Mixture versus substance

information

Not an aspiration hazard. No information available.

11.2. Information on other hazards

**Endocrine disrupting** 

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Other information Not available.

# **SECTION 12: Ecological information**

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

Components **Species Test Results** 

(R)-p-Mentha-1,8-diene (CAS 5989-27-5)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia pulex) 69,6 mg/l, 48 hours

LC50 Fathead minnow (Pimephales promelas) >= 0,619 - <= 0,796 mg/l, 96 hours Fish

Ethyl alcohol (CAS 64-17-5)

Aquatic

Acute

EC50 Crustacea Water flea (Daphnia magna) >= 7,7 - <= 11,2 mg/l, 48 hours

LC50 Fish Rainbow trout, donaldson trout 42 mg/l, 4 days

(Oncorhynchus mykiss)

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

## 12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

(R)-p-Mentha-1,8-diene 4.57 Ethyl alcohol -0,31

Not available.

**Bioconcentration factor (BCF)** 

Not established. 12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects None known.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Dispose of in accordance with local regulations. Empty containers or liners may retain some Residual waste

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Material name: Sani Luxe Hand Sanitizer Gel

#### **SECTION 14: Transport information**

```
ADR
```

14.1. UN number 14.2. UN proper shipping ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) name 14.3. Transport hazard class(es) **Class** 3 Subsidiary risk 3 Label(s) Hazard No. (ADR) 30 D/E **Tunnel restriction code** Ш 14.4. Packing group 14.5. Environmental hazards No. Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user RID 14.1. UN number UN1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 3 Subsidiary risk 3 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No. Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user  $\Delta DN$ 14.1. UN number UN1170 14.2. UN proper shipping ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) name 14.3. Transport hazard class(es) Class 3 Subsidiary risk 3 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user IATA UN1170 14.1. UN number 14.2. UN proper shipping Ethanol solutions 14.3. Transport hazard class(es) Class 3 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards No. **ERG Code** Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user Other information Allowed with restrictions. Passenger and cargo aircraft Allowed with restrictions. Cargo aircraft only **IMDG** 14.1. UN number UN1170 14.2. UN proper shipping ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) name 14.3. Transport hazard class(es) **Class** 3 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards No. Marine pollutant

F-E, S-D

**EmS** 

14.6. Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk

This product is not intended to be transported in bulk.

according to IMO instruments ADN; ADR; IATA; IMDG; RID



# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

EU Regulation 648/2004, Annex VII, Content Labeling for Detergents

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

## **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

#### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

(R)-p-Mentha-1.8-diene (CAS 5989-27-5)

Ethyl alcohol (CAS 64-17-5)

Other regulations Product is regulated as a hand sanitizer and information in Section 2 will not match product label.

> The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as National regulations

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

#### References ECHA registered substances database

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eve irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision information Product and Company Identification: Product Codes

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties

Transport Information: Product Shipping Name/Packing Group

Regulatory Information: Other

HazReg Data: International Inventories

GHS: Classification

# Training information Disclaimer

Follow training instructions when handling this material.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Celeste Industries cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Material name: Sani Luxe Hand Sanitizer Gel